



SP ATF D6

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

SP ATF D6 is a premium automatic transmission fluid with Durafilm Technology designed for modern automatic transmissions. This advanced technology extends transmission life through a durable oil film, providing a smooth driving experience for an extended period.



APPLICATION

SP ATF D6 is recommended for:

- ✓ Automatic transmissions for passenger cars and heavy-duty trucks require standards according to the recommended table.
- ✓ Power steering components.
- ✓ Some hydraulic applications require viscosity of ISO VG 32-46.

STANDARD

JASO M315 Type 1A-LV
 Honda ATF DW-1, Z1
 GM W16444, DEXRON-VI
 Ford P/N XT-10-QLV
 MERCON LV
 Chrysler Type 9602
 Chrysler NAG2
 ZF TE-ML 11
 Toyota T-III, T-IV ASD
 Mazda ATF M-III, M-V, ZF
 Nissan Matic D, J, S
 Suzuki AT Oil 5D06, 2384K
 Subaru F6, Red 1
 AMMIX ATF D-III Multi, D3-SP
 Hyundai/Kia SP III, SP IV

Standards for 6-speed automatic transmissions in Audi, BMW, Mini-Cooper, Jaguar, Peugeot/Citroen, Saab, Volvo, Porsche, and all vehicles requiring DEXRON III or Mercon SP fluid.

BENEFITS

• Friction modifier

Enhances the smoothness and dependability of automotive drivetrain operation, contributing to a comfortable driving feel.

• Excellent oxidation resistance

Prevents oil sludge formation caused by heat, maintaining a durable lubricant film.

• High viscosity index

Optimizes performance and minimizes power loss over a wide temperature range.

• Superior anti-wear properties

Specially formulated additives offer excellent wear protection for extended transmission life.

**TYPICAL SPECIFICATION**

Specification	Test Method	Unit	Value
Kinematic Viscosity @ 100°C	ASTM D445	cSt	6,5 ÷ 6,9
Viscosity Index	ASTM D2270	--	Min 150
Flash Point	ASTM D92	°C	Min 200
Pour Point	ASTM D97	°C	Max -30
Water Content	ASTM D95	%v	Max 0.05
Density @ 15°C	ASTM D4052	g/cm ³	0.83-0.85
Color	Visual	--	Red
Appearance	Visual	--	Bright & clear

* Minor variations in product typical test data are to be accepted in normal manufacturing

PACKING

18L 200L 1000L As required

ENVIRONMENT, HEALTH & SAFETY**•Health & safety**

SP ATF D6 does not pose any significant health hazard when used according to instructions and in compliance with personal and industrial hygiene standards.

Avoid contact with skin. Use impermeable gloves with used oil. If skin contact occurs, wash immediately with soap and water.

•Protect the environment

Collect used oil to designated collection points. Do not discharge into sewers, ground or water sources.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet (MSDS), which can be obtained from <http://www.apsaigonpetro.com>

STORAGE

Storage temperature: Less than 60°C. Avoid direct sunlight.

Keep away from heat sources and sources of ignition, avoid water contamination, and do not mix with other oils.

ADDITIONAL INFORMATION**▪ Technical assistance**

For more information, visit our website www.apsaigonpetro.com. Hotline: 1900 0104