



SP UTTO 10W-30

UNIVERSAL TRACTOR TRANSMISSION OIL

DESCRIPTION

SP UTTO 10W-30 is a premium universal tractor transmission oil (UTTO), formulated with high-performance base oils and advanced additives. It is specifically designed for applications in agriculture, construction, and forestry. SP UTTO provides exceptional protection from engine startups to sustain heavy-duty operation.

APPLICATION

SP UTTO 10W-30 is suitable for a wide range of applications, including gear transmissions, rear axles, wet brakes, power take-offs (PTO), and hydraulic systems in tractors, combines, loaders, skid steers, and off-road equipment.

SP UTTO 10W-30 is recommended for agricultural machinery from renowned manufacturers such as KUBOTA, CATERPILLAR, FORD, ALLISON, JOHN DEERE, and MASSEY FERGUSON.

PROPERTIES

- Ford M2C 134D
- Case New Holland MAT 3525 & 3526
- John Deere J20C
- Massey Ferguson CMS M1143, 1135 & 1145
- ZF TE ML 03E & 05E
- KUBOTA UDT
- API GL-4
- Volvo WB101...

BENEFITS

- Optimizes clutch performance and wet brake systems.
- Enhances hydraulic system efficiency.
- Provides superior corrosion protection for gears, bearings, and non-ferrous metals in the equipment.
- Ensures stability under all operating temperatures, reducing noise and providing smooth shifting.



TYPICAL SPECIFICATION

Specification	Test Method	Unit	Value
Kinematic Viscosity @40°C	ASTM D445	cSt	Min 52,0
Kinematic Viscosity @100°C	ASTM D445	cSt	13,5 – 18,4
Viscosity Index	ASTM D2270	--	Min 135
Flash Point (COC)	ASTM D92	°C	Min 210
Pour Point	ASTM D97	°C	Max -30
Foam Tendency @93.5°C (SeqII)	ASTM D892	ml/ml	Max 50/0

* Minor variations in product typical test data are to be excepted in normal manufacturing

**PACKING**

18L 200L 1000L As required

ENVIRONMENT, HEALTH & SAFETY**•Health & safety**

SP UTTO 10W-30 does not pose any significant health hazard when used according to instructions and in compliance with personal and industrial hygiene standards.

Avoid contact with skin. Use impermeable gloves with used oil. If skin contact occurs, wash immediately with soap and water.

•Protect the environment

Collect used oil to designated collection points. Do not discharge into sewers, ground or water sources.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet (MSDS), which can be obtained from <http://www.apsaigonpetro.com>

STORAGE

Storage temperature: Less than 60°C. Avoid direct sunlight.

Keep away from heat sources and sources of ignition, avoid water contamination, and do not mix with other oils.

▪ Technical assistance

For more information, visit our website www.apsaigonpetro.com. Hotline: 1900 0104